

# BME ACTIVECORE™

## Glass Door Chiller

### Display / Bottom Mount

A new glass door chiller combining SKOPE's revolutionary new ActiveCore technology with a modern frameless aesthetic design. These models provide market leading energy savings along with new features to deliver optimal performance, efficiency and reliability.

#### Options

Available in 1 and 2 door models  
Additional shelves  
Illuminated sign panel

#### SIGNIFICANT ENERGY SAVINGS

Uses 35% less energy than the previous B1200G-2 model, saving more than \$266 per year\*

Significantly reduced noise and improved quality, for quieter operation

Patented easy to install shelf clip and numbered shelf support strip, reduces set up time and enables finer adjustments

A frameless glass door design with aluminium trim

Redesigned kick panel for branding opportunities and easy access to filter for maintenance

Fitted with lock tabs for extra security

Optimal airflow and cooling performance reduces temperature variations and energy consumption

Split shelving system for improved product presentation

Premium energy efficient glass using new low-emissivity coating technology, equivalent to double Low-E performance. An invisible finish ensures maximum visual clarity\*\*

Ergonomically designed, brushed stainless steel handles

New slotted back panel design allows chilled airflow to be pushed directly on the product

Updated controller with manual light switch

Revolutionary ActiveCore refrigeration system



Available in white only



**Warranty**  
2 year protection



**High Energy  
Efficiency**





ActiveCore™

# Specifications

**SKOPE®**

## BME ActiveCore™ Display / Bottom Mount





Integral front elevation

### BME600-A - GLASS DOOR

Model	Weight (kg)	Integral/Remote	Chiller/Freezer	Gross Volume 584 litres Total Shelf Area 1.62m <sup>2</sup> Floor Area 0.63m <sup>2</sup> (inc. 50mm stand-off)	BME600-A 1 DOOR
<b>BME600-A</b>	185	Integral	Chiller		
		Integral External (mm)	Internal (mm)		
<b>Height</b>		1995	1454		
<b>Width</b>		740	640		
<b>Depth***</b>		795	602		
<b>Door Height</b>		1536			
<b>Glass Area</b>		0.92m <sup>2</sup>			

- 4.35 MEPS (kWh/24h/m<sup>2</sup>)
- Maximum height 2195mm with optional sign panel fitted
- +1°C to +4°C in 43°C ambient



Integral front elevation

### BME1200-A - GLASS DOORS

Model	Weight (kg)	Integral/Remote	Chiller/Freezer	Gross Volume 1079 litres Total Shelf Area 3.00m <sup>2</sup> Floor Area 1.08m <sup>2</sup> (inc. 50mm stand-off)	BME1200-A 2 DOOR
<b>BME1200-A</b>	245	Integral	Chiller		
		Integral External (mm)	Internal (mm)		
<b>Height</b>		1995	1454		
<b>Width</b>		1280	1180		
<b>Depth***</b>		795	602		
<b>Door Height</b>		1536			
<b>Glass Area</b>		1.57 m <sup>2</sup>			

- 3.86 MEPS (kWh/24h/m<sup>2</sup>)
- Maximum height 2195mm with optional sign panel fitted
- +1°C to +4°C in 43°C ambient

\*Based on 30 cents per kW. Calculated using 4.55 kWh/24h(TEC) no illuminated sign panel.

\*\*For tropical installations please speak to a SKOPE representative.

\*\*\*Total depth includes removable 50mm handles, and excludes 50mm retractable stand-off.